




SERIES

CS

PumpAgents.com  
Wholesale Pump Agents

## CLOSE COUPLED TURBINE PUMPS



**4CS- 1725 RPM - 60Hz.**

**CS - 3450 RPM - 60Hz.**

(See Individual curves for symbol number)

| * MAXIMUM HEAD |       |                |           |
|----------------|-------|----------------|-----------|
| Symbol No.     | H.P.  | Catalog Number |           |
|                |       | 1 - Phase      | 3 - Phase |
| 1              | 1/3   | 34CS5M         | 334CS5M   |
| 2              | 1/3   | 34CS6M         | 334CS6M   |
| 3              | 1/2   | 54CS6M         | 354CS6M   |
| 4              | 1/3   | 34CS7M         | 334CS7M   |
| 5              | 1/2   | 54CS7M         | 354CS7M   |
| 6              | 1/2   | 54CS8M         | 354CS8M   |
| 7              | 1     | 10CS5M         | 310CS5M   |
| 8              | 1 1/2 | 15CS5M         | 315CS5M   |
| 9              | 1     | 10CS6M         | 310CS6M   |
| 10             | 1 1/2 | 15CS6M         | 315CS6M   |
| 11             | 2     | 20CS6M         | 320CS6M   |
| 12             | 1 1/2 | 15CS7M         | 315CS7M   |
| 13             | 2     | 20CS7M         | 320CS7M   |
| 14             | 3     | ---            | 330CS7M   |
| 15             | 2     | 20CS8M         | 320CS8M   |
| 16             | 3     | ---            | 330CS8M   |
| 17             | 5     | ---            | 350CS8M   |
| 18             | 3     | ---            | 330CS9M   |
| 19             | 5     | ---            | 350CS9M   |

**CS - 2900 RPM - 50Hz.**



(See Individual curves for symbol number)

| MAXIMUM HEAD |      |                |
|--------------|------|----------------|
| Symbol No.   | H.P. | Catalog Number |
| * 1          | 2.0  | L320CS9M       |
| 2            | 2.6  | L330CS9M       |
| 3            | 4.0  | L340CS9M       |
| 4            | 1.5  | L315CS8M       |
| * 5          | 2.0  | L320CS8M       |
| 6            | 2.6  | L330CS8M       |
| 7            | 1.5  | L315CS7M       |
| * 8          | 2.0  | L320CS7M       |
| 9            | 2.6  | L330CS7M       |
| 10           | 1.0  | L310CS6M       |
| 11           | 1.5  | L315CS6M       |
| * 12         | 2.0  | L320CS6M       |
| 13           | 1.0  | L310CS5M       |
| 14           | 1.0  | L315CS5M       |

\* Pump numbers 1, 5, 8 & 12 are the only pumps available in single phase 115/230 volt.

All of the pump above are available with stuffing box.

\* For Standard Pumps with ODP Motors



PUMPS & SYSTEMS

A Crane Co. Company

PumpAgents.com - buy pumps and parts online


**CLOSE COUPLED TURBINE PUMPS**

| Catalog Number |         | HP      | Tappings       |                 | PSI FEET | TOTAL HEAD         |      |      |      |      |      |      |      |      |       |       |      |       |       |     |
|----------------|---------|---------|----------------|-----------------|----------|--------------------|------|------|------|------|------|------|------|------|-------|-------|------|-------|-------|-----|
|                |         |         | Suct. NPT (in) | Disch. NPT (in) |          | 8.6                | 17.2 | 26   | 43.3 | 54.1 | 64.9 | 75.8 | 86.6 | 97.4 | 108.3 | 119.1 | 130  | 140.1 | 151.6 |     |
|                |         |         |                |                 |          | 20                 | 40   | 60   | 100  | 125  | 150  | 175  | 200  | 225  | 250   | 275   | 300  | 325   | 350   |     |
|                |         |         |                |                 |          | CAPACITY IN G.P.M. |      |      |      |      |      |      |      |      |       |       |      |       |       |     |
| 1-Phase        | 3-Phase |         |                |                 |          |                    |      |      |      |      |      |      |      |      |       |       |      |       |       |     |
| 1750 RPM       | 34CS5M  | 334CS5M | 1/3            | 1 1/4           | 1        |                    | 5.8  | 4.9  | 4.3  | 3.3  | 2.8  | 2.4  | 2.1  | 1.8  | 1.6   |       |      |       |       |     |
|                | 34CS6M  | 334CS6M | 1/3            |                 |          |                    | 7.8  | 6.9  | 6.3  | 5.2  | 4.6  | 4.1  | 3.7  | 3.3  |       |       |      |       |       |     |
|                | 54CS6M  | 354CS6M | 1/2            |                 |          |                    | 7.8  | 6.9  | 6.3  | 5.2  | 4.6  | 4.1  | 3.7  | 3.3  | 2.9   | 2.6   | 2.3  |       |       |     |
|                | 34CS7M  | 334CS7M | 1/3            |                 |          |                    | 10.4 | 9.4  | 8.5  | 7.2  | 6.5  |      |      |      |       |       |      |       |       |     |
|                | 54CS7M  | 354CS7M | 1/2            |                 |          |                    | 10.4 | 9.4  | 8.5  | 7.2  | 6.5  | 5.9  | 5.4  |      |       |       |      |       |       |     |
| 54CS8M         | 354CS8M | 1/2     |                |                 |          | 12.2               | 11.3 | 10.4 | 9.0  | 8.2  |      |      |      |      |       |       |      |       |       |     |
| 3450 RPM       | 10CS5M  | 310CS5M | 1              | 1 1/4           | 1        |                    | 11   | 10.6 | 10.1 | 9.3  | 9    | 8.5  | 8.2  | 8    | 7.7   |       |      |       |       |     |
|                | 15CS5M  | 315CS5M | 1 1/2          |                 |          |                    | 11   | 10.6 | 10.1 | 9.3  | 9    | 8.5  | 8.2  | 8    | 7.7   | 7.5   | 7.4  | 7.2   | 7.1   |     |
|                | 10CS6M  | 310CS6M | 1              |                 |          |                    | 16   | 15.2 | 14.5 | 13.5 | 12.8 |      |      |      |       |       |      |       |       |     |
|                | 15CS6M  | 315CS6M | 1 1/2          |                 |          |                    | 16   | 15.2 | 14.5 | 13.5 | 12.8 | 12.4 | 12   | 11.5 | 11    | 10.7  |      |       |       |     |
|                | 20CS6M  | 320CS6M | 2              |                 |          |                    | 16   | 15.2 | 14.5 | 13.5 | 12.8 | 12.4 | 12   | 11.5 | 11    | 10.7  | 10.5 | 10.1  | 9.7   | 9.5 |
|                | 15CS7M  | 315CS7M | 1 1/2          |                 |          |                    | 20.5 | 19.6 | 19.5 | 17.3 |      |      |      |      |       |       |      |       |       |     |
|                | 20CS7M  | 320CS7M | 2              |                 |          |                    | 20.5 | 19.6 | 19.5 | 17.3 | 16.5 | 16   | 15.3 | 14.7 |       |       |      |       |       |     |
|                | ---     | 330CS7M | 3              |                 |          |                    | 20.5 | 19.6 | 19.5 | 17.3 | 16.5 | 16   | 15.3 | 14.7 | 14.2  | 13.7  | 13.3 | 12.8  | 12.5  | 12  |
|                | 20CS8M  | 320CS8M | 2              |                 |          |                    | 26.5 | 25.5 | 24.6 | 23   | 22   |      |      |      |       |       |      |       |       |     |
|                | ---     | 330CS8M | 3              |                 |          |                    | 26.5 | 25.5 | 24.6 | 23   | 22   | 21.3 | 20.5 | 19.8 | 19.2  |       |      |       |       |     |
| ---            | 350CS8M | 5       |                | 26.5            | 25.5     | 24.6               | 23   | 22   | 21.3 | 20.5 | 19.8 | 19.2 | 18.5 | 18   | 17.4  | 16.8  | 16.3 |       |       |     |
| ---            | 330CS9M | 3       |                |                 |          | 32.5               | 31.5 | 30.5 | 28.6 | 27.5 | 26.5 | 25.6 | 24.7 | 23.8 | 23    | 22.2  | 21.5 | 20.7  | 20    |     |
| ---            | 350CS9M | 5       |                |                 |          | 32.5               | 31.5 | 30.5 | 28.6 | 27.5 | 26.5 | 25.6 | 24.7 | 23.8 | 23    | 22.2  | 21.5 | 20.7  | 20    |     |

| Catalog Number |         | HP      | Tappings       |                 | TOTAL HEAD         |      |      |      |      |      |      |      |      |      |      |      |      |      |       |      |
|----------------|---------|---------|----------------|-----------------|--------------------|------|------|------|------|------|------|------|------|------|------|------|------|------|-------|------|
|                |         |         | Suct. NPT (in) | Disch. NPT (in) | kPa                | 59   | 119  | 179  | 299  | 373  | 447  | 523  | 597  | 672  | 747  | 821  | 896  | 966  | 1045  |      |
|                |         |         |                |                 | Meters             | 6.1  | 12.1 | 18.2 | 30.5 | 38.1 | 45.7 | 53.3 | 61.0 | 68.6 | 76.2 | 83.8 | 91.4 | 99.1 | 106.6 |      |
|                |         |         |                |                 | CAPACITY IN L.P.S. |      |      |      |      |      |      |      |      |      |      |      |      |      |       |      |
| 1-Phase        | 3-Phase |         |                |                 |                    |      |      |      |      |      |      |      |      |      |      |      |      |      |       |      |
| 1750 RPM       | 34CS5M  | 334CS5M | 1/3            | 1 1/4           | 1                  |      | 0.36 | 0.30 | 0.27 | 0.20 | 0.17 | 0.15 | 0.13 | 0.11 | 1.6  |      |      |      |       |      |
|                | 34CS6M  | 334CS6M | 1/3            |                 |                    |      | 0.49 | 0.43 | 0.39 | 0.32 | 0.29 | 0.25 | 0.23 | 0.20 |      |      |      |      |       |      |
|                | 54CS6M  | 354CS6M | 1/2            |                 |                    |      | 0.49 | 0.43 | 0.39 | 0.32 | 0.29 | 0.25 | 0.23 | 0.20 | 0.18 | 0.16 | 0.14 |      |       |      |
|                | 34CS7M  | 334CS7M | 1/3            |                 |                    |      | 0.65 | 0.59 | 0.53 | 0.45 | 0.41 |      |      |      |      |      |      |      |       |      |
|                | 54CS7M  | 354CS7M | 1/2            |                 |                    |      | 0.65 | 0.59 | 0.53 | 0.45 | 0.41 | 0.37 | 0.34 |      |      |      |      |      |       |      |
| 54CS8M         | 354CS8M | 1/2     |                |                 |                    | 0.76 | 0.71 | 0.65 | 0.56 | 0.51 |      |      |      |      |      |      |      |      |       |      |
| 3450 RPM       | 10CS5M  | 310CS5M | 1              | 1 1/4           | 1                  |      | 0.69 | 0.66 | 0.63 | 0.58 | 0.56 | 0.53 | 0.51 | 0.50 | 0.48 |      |      |      |       |      |
|                | 15CS5M  | 315CS5M | 1 1/2          |                 |                    |      | 0.69 | 0.66 | 0.63 | 0.58 | 0.56 | 0.53 | 0.51 | 0.50 | 0.48 | 0.47 | 0.46 | 0.45 | 0.44  |      |
|                | 10CS6M  | 310CS6M | 1              |                 |                    |      | 1.00 | 0.95 | 0.91 | 0.85 | 0.80 |      |      |      |      |      |      |      |       |      |
|                | 15CS6M  | 315CS6M | 1 1/2          |                 |                    |      | 1.00 | 0.95 | 0.91 | 0.85 | 0.80 | 0.78 | 0.75 | 0.72 | 0.69 | 0.67 |      |      |       |      |
|                | 20CS6M  | 320CS6M | 2              |                 |                    |      | 1.00 | 0.95 | 0.91 | 0.85 | 0.80 | 0.78 | 0.75 | 0.72 | 0.69 | 0.67 | 0.66 | 0.63 | 0.61  | 0.59 |
|                | 15CS7M  | 315CS7M | 1 1/2          |                 |                    |      | 1.29 | 1.24 | 1.23 | 1.09 |      |      |      |      |      |      |      |      |       |      |
|                | 20CS7M  | 320CS7M | 2              |                 |                    |      | 1.29 | 1.24 | 1.23 | 1.09 | 1.04 | 1.00 | 0.96 | 0.92 |      |      |      |      |       |      |
|                | ---     | 330CS7M | 3              |                 |                    |      | 1.29 | 1.24 | 1.23 | 1.09 | 1.04 | 1.00 | 0.96 | 0.92 | 0.89 | 0.86 | 0.83 | 0.80 | 0.78  | 0.75 |
|                | 20CS8M  | 320CS8M | 2              |                 |                    |      | 1.67 | 1.60 | 1.55 | 1.45 | 1.38 |      |      |      |      |      |      |      |       |      |
|                | ---     | 330CS8M | 3              |                 |                    |      | 1.67 | 1.60 | 1.55 | 1.45 | 1.38 | 1.34 | 1.29 | 1.24 | 1.21 |      |      |      |       |      |
|                | ---     | 350CS8M | 5              |                 |                    |      | 1.67 | 1.60 | 1.55 | 1.45 | 1.38 | 1.34 | 1.29 | 1.24 | 1.21 | 1.16 | 1.13 | 1.09 | 1.05  | 1.02 |
|                | ---     | 330CS9M | 3              |                 |                    |      | 2.05 | 1.98 | 1.92 | 1.80 | 1.73 | 1.67 |      |      |      |      |      |      |       |      |
|                | ---     | 350CS9M | 5              |                 |                    |      | 2.05 | 1.98 | 1.92 | 1.80 | 1.73 | 1.67 | 1.61 | 1.55 | 1.50 | 1.45 | 1.40 | 1.35 | 1.30  | 1.26 |

**NOTE:** When pumping hot water over 180°F (82.2°C), check the NPSH available in the pumping system against the required pump NPSH shown on pump performance curves. Available NPSH must be greater than required NPSH.

## FEATURES



**BURKS** exclusive unique regenerative type turbine pumps are designed to handle clear water and many other non-abrasive, lower viscosity liquids on high pressure, low capacity applications with the greatest possible efficiency.

**BURKS** is the only turbine pump with Life-Lok ® External Impeller Adjustment feature that allows readjustment of impeller without disturbing piping, disassembling pump or replacing parts. Gives up to 40% longer service life than turbine pumps of other designs.

- Self-Priming
- Compact, Space-saving size
- No coupling - eliminates misalignment problems
- Dependable carbon/ceramic mechanical shaft seal for temperatures to 225°F (107°C).
- Bronze impeller with Monel blades - the only moving part
- Bronze raceway with cast-in vortex pockets - will not vapor lock
- #303 Stainless Steel pump shaft
- Easy to service
- Every pump factory tested
- Available Bronze fitted, All Bronze, Stainless Steel

### MAXIMUM OPERATING CONDITIONS

|                                           |                   |
|-------------------------------------------|-------------------|
| TEMPERATURE<br>(For Standard Buna-N Seal) | 225°F (107°C)     |
| INLET PRESSURE                            | 100 PSI (690kPa)  |
| CASING WORKING PRESSURE                   | 250 PSI (1723kPa) |

### MOTOR INFORMATION

#### 4CS Series:

**Single Phase** motors are 115/208-230 Volt, 60Hz, 1750RPM

**Three Phase** motors are 208-230/460 Volts, 60/50Hz, 1750/1450RPM

#### CS Series:

**Single Phase** motors are 115/208-230 Volt, 60 Hz, 3450RPM

**Three Phase** 1, 1½ & 2HP. - 208-230/460 Volt, 60/50 Hz., 3450/2900 RPM

**Three Phase** 3 & 5 HP - 208-230/460 Volt, 60 Hz, 3450RPM

Standard pump motors have open drip proof construction and are rated with jet pump service factors for continuous duty operation at all ratings shown.

**Single phase** motors are capacitor start/induction run with built-in overload protection.

**Three phase** motors require a magnetic type starter which provides full 3-leg overload protection. Failure to use the correct starter and overloads will void the warranty.


### FOR TEMPERATURES TO 500°F (260°C).

Series CS Pumps are available in a Jacketed Seal Cavity design for pumping hot oil, hot water and heat transfer fluids in common use in high temperature heating or cooling applications. This feature greatly extends seal life in high temperature applications. To order, add suffix "J" to pump catalog number for temperatures below 400°F (204°C) and add suffix "JK" to pump catalog number for temperatures over 400°F (204°C). Example: 15CS5MJ. See Section on High Temperature Pumps for more information.

### MATERIALS OF CONSTRUCTION

| PART       | BRONZE FITTED                     | ALL BRONZE                        | STAINLESS STEEL                   |
|------------|-----------------------------------|-----------------------------------|-----------------------------------|
| Frame      | Cast Iron                         | Bronze                            | #316 Stainless                    |
| Case       | Cast Iron                         | Bronze                            | #316 Stainless                    |
| Impeller   | Bronze<br>(Monel Blades)          | Bronze<br>(Monel Blades)          | #303 Stainless                    |
| Raceway    | Bronze                            | Bronze                            | #303 Stainless                    |
| Shaft      | #303 Stainless                    | #303 Stainless                    | #303 Stainless                    |
| Shaft Seal | Carbon-Ceramic<br>S. Steel-Buna-N | Carbon-Ceramic<br>S. Steel-Buna-N | Carbon-Ceramic<br>S. Steel-Buna-N |

## DIMENSIONS





| SERIES | HP    | Tappings       |                | DIMENSIONS IN INCHES |          |       |         |        |   |   |       |       |       |        |       |
|--------|-------|----------------|----------------|----------------------|----------|-------|---------|--------|---|---|-------|-------|-------|--------|-------|
|        |       | Disc. NPT (in) | Suct. NPT (in) | 1 PH A               | 3 PH A   | B     | 1 PH C  | 3 PH C | D | E | F     | G     | H     | J      | K     |
| 4CS    | 1/3   | 1 1/4          | 1              | 17 5/8               | 16 3/8   | 6 1/2 | 6 5/8   | 6 5/8  | 3 | 9 | 1 3/4 | 6 3/4 | 3 1/2 | 2 7/16 | 3 1/4 |
|        | 1/2   | 1 1/4          | 1              | 17 5/8               | 16 5/8   | 6 1/2 | 6 5/8   | 6 5/8  | 3 | 9 | 1 3/4 | 6 3/4 | 3 1/2 | 2 7/16 | 3 1/4 |
| CS     | 1     | 1 1/4          | 1              | 18 5/16              | 18 5/16  | 6 1/2 | 6 5/8   | 6 5/8  | 3 | 9 | 1 3/4 | 6 3/4 | 3 1/2 | 2 7/16 | 3 1/4 |
|        | 1 1/2 | 1 1/4          | 1              | 19 1/16              | 19 1/16  | 6 1/2 | 8 13/16 | 6 5/8  | 3 | 9 | 1 3/4 | 6 3/4 | 3 1/2 | 2 7/16 | 3 1/4 |
|        | 2     | 1 1/4          | 1              | 19 9/16              | 19 1/16  | 6 1/2 | 8 13/16 | 6 5/8  | 3 | 9 | 1 3/4 | 6 3/4 | 3 1/2 | 2 7/16 | 3 1/4 |
|        | 3     | 1 1/4          | 1              | ---                  | 19 9/16  | 6 1/2 | ---     | 6 5/8  | 3 | 9 | 1 3/4 | 6 3/4 | 3 1/2 | 2 7/16 | 3 1/4 |
|        | 5     | 1 1/4          | 1              | ---                  | 20 15/16 | 6 1/2 | ---     | 6 5/8  | 3 | 9 | 1 3/4 | 6 3/4 | 3 1/2 | 2 7/16 | 3 1/4 |

| SERIES | HP    | Tappings       |                | DIMENSIONS IN MILLIMETERS |        |     |        |        |    |     |    |     |    |    |    |
|--------|-------|----------------|----------------|---------------------------|--------|-----|--------|--------|----|-----|----|-----|----|----|----|
|        |       | Disc. NPT (in) | Suct. NPT (in) | 1 PH A                    | 3 PH A | B   | 1 PH C | 3 PH C | D  | E   | F  | G   | H  | J  | K  |
| 4CS    | 1/3   | 1 1/4          | 1              | 447                       | 415    | 165 | 168    | 168    | 76 | 228 | 44 | 171 | 89 | 62 | 82 |
|        | 1/2   | 1 1/4          | 1              | 447                       | 422    | 165 | 168    | 168    | 76 | 228 | 44 | 171 | 89 | 62 | 82 |
| CS     | 1     | 1 1/4          | 1              | 465                       | 465    | 165 | 168    | 168    | 76 | 228 | 44 | 171 | 89 | 62 | 82 |
|        | 1-1/2 | 1 1/4          | 1              | 484                       | 484    | 165 | 223    | 168    | 76 | 228 | 44 | 171 | 89 | 62 | 82 |
|        | 2     | 1 1/4          | 1              | 496                       | 484    | 165 | 223    | 168    | 76 | 228 | 44 | 171 | 89 | 62 | 82 |
|        | 3     | 1 1/4          | 1              | ---                       | 496    | 165 | ---    | 168    | 76 | 228 | 44 | 171 | 89 | 62 | 82 |
|        | 5     | 1 1/4          | 1              | ---                       | 531    | 165 | ---    | 168    | 76 | 228 | 44 | 171 | 89 | 62 | 82 |

A strainer, approximately 20 mesh, should be installed on the suction side of the pump to prevent chips, scale or hard foreign particales from entering the pump and damaging the raceway and impeller.

**CS SERIES CLOSE COUPLED TURBINE PUMPS**



---

For technical advice or service please take your pump into your local pump service center.

To order pump or parts or for pricing please go to the following links :

[Burks Pumps Home >>](#)

[Burks Pumps stock list >>](#)