



PumpAgents.com - Click here for Pricing/Ordering

JABSCO®

59500-Series

GB COMMERCIAL CIRCULATION PUMP

- 15 litres/min @ 0.12 Bar
- Magnetic Drive - sealed pump chamber
- Ignition protected (ISO8846 MARINE)
- Meets EMC requirements
- Connections for 19mm (3/4") ID Hose
- Continuously rated
- Pumps water at 100°C
- Handles aggressive liquids
- Supplied complete with mounting bracket

D KREISELPUMPE FÜR GEWERBLICHEN EINSATZ

- 15 l/min bei 0,12 bar Gegendruck
- Magnetkupplung - Pumpengehäuse abgedichtet
- Funkengeschützt nach ISO 8846
- Entspricht den EMC-Vorschriften
- Anschlüsse für 19-mm-Schlauch (3/4")
- Dauerlauf-geeignet
- Fördert Wasser bis 100°C
- Verpumpt auch aggressive Flüssigkeiten
- Wird komplett mit Halterung geliefert

NL COMMERCIELE CIRCULATIE POMP

- 15 liter/min. Bij 0.12 Bar
- Magnetisch gedreven - afgedichte pompkamer
- Beveiligd tegen vonken (ISO8846 MARINE)
- Volgt EMC richtlijn
- Aansluitingen voor 19mm (3/4") Inw. Slang
- Continu werkend
- Pompt water bij 100°C
- Verpompt agressieve vloeistoffen
- Levering compleet met montage beugel

E BOMBA RECIRCULADORA

- 15 litros/min
- Arrastre magnético - cuerpo aislado
- Antideflagrante (ISO 8846 MARINE)
- Cumple con lasmas EMC
- Conexiones para 19mm (3/4") tubo
- Trabajo en continuo
- Bombea agua a 100°C
- Bombea líquidos agresivos
- Equipado con soportes

S CIRKULATIONSUMP FÖR PROFFESIONELLT BRUK

- 15 liter/min @ 0.12 bar
- Magnetdriven - helt slutet pumphus
- Gnistsäker (ISO 8846 MARIN)
- Svarar mot EMC direktivet
- Anslutningar för invändig 19 mm (3/4") slang
- Avsedd för kontinuerlig drift
- Pumpar vatten upp till 100°C
- Klarar aggressiva vätskor
- Levereras komplett med monteringsfot

F POMPE DE CIRCULATION

- 15 litres/mn à 0.12 bar
- Entraînement magnétique - Pompe monobloc
- Protégée contre l'ignition (ISO 8846 MARINE)
- Conforme aux spécifications EMC
- Raccords pour tuyaux 19 mm (3/4") de diamètre intérieur
- Usage continu
- Capable de pomper de l'eau à 100°C
- Supporte les liquides agressifs
- Fournie avec étrier de fixation

I POMPE COMMERCIALI

- 15 litri/min. 0.12 bar
- Camera della pompa sigillata-girante a trascinamento magnetico
- Protezione antideflagrante ISO 8846
- Attenersi a EMC
- Raccordi per tubi con diametro interno di 19mm (3/4")
- Adatta per acqua a 100°C
- Adatta per liquidi corrosivi
- Fornita completa di staffa di montaggio

Model No.	Voltage	Fuse Size	Current Draw	Cable Length*	Minimum Wire Size	
59500-0012	12 V DC	2A	1.2A	0 - 8 m (0 - 27 ft) 8 - 15 m (27 - 50 ft)	2.5 mm ² 4.0 mm ²	AWG 12 AWG 10
59500-0024	24 V DC	1A	0.7A	0 - 8 m (0 - 27 ft) 8 - 15 m (27 - 50 ft)	1.5mm ² 2.5mm ²	AWG 14 AWG 12

* Cable length is the total distance from the battery to the pump and back to the battery.



For technical advice or service please take your pump into your local pump service center.
To order pump or parts or for pricing please go to the following links :

[Jabsco Pumps Home >>](#)

[Jabsco Pumps stock list >>](#)