

5-MSP SERIES



Features


- Epoxy coated die-cast aluminum housing
- Oil-filled motor
- 26.3' maximum lift
- 380 watts
- 1" FNPT discharge
- Thermal overload protection
- For submersible use only


Construction

- Motor 1/6 HP Oil Filled
- Intermittent Liquid Temp. up to 120° F
- Intake Screened
- Discharge 1" FNPT
- Housing Epoxy coated cast aluminum
- Cover Epoxy coated cast aluminum
- Volute Nylon
- Impeller Nylon
- Shaft Seal Viton®
- Screen Nylon

Little Giant's most versatile portable utility pump with oil-filled motor and epoxy coated cast aluminum housing. For commercial, industrial and home applications including statuary fountains, water displays, air conditioners, machine tool coolants, and many other applications where liquid must be transferred or

5-MSP SERIES





Specifications

5

0

										Performance (GPH @ Head)				ead)	Shut Off		Pwr. Cord	Weight
Model No.	Item No.	Discharge	Intake	Listing(s)	HP	Volts	Hertz	Amps	Watts	1'	3'	5'	10'	20'	Feet	PSI	(ft)	(Lbs.)
5-MSP	505000	1" FNPT	Screened	UL	1/6	115	60	5.0	380	1200	1170	1100	1000	520	26.3	11.4	10	8.25
5-MSP	505086	1" FNPT	Screened	UL/CSA	1/6	115	60	5.0	380	1200	1170	1100	1000	520	26.3	11.4	10	8.25
5-MSP	505176	1" FNPT	Screened	UL/CSA	1/6	115	60	5.0	380	1200	1170	1100	1000	520	26.3	11.4	18	8.50
5-MSP	505025	1" FNPT	Screened	UL	1/6	115	60	5.0	380	1200	1170	1100	1000	520	26.3	11.4	25	8.75
5-MSP	505500	1" FNPT	Screened		1/6	127	60	5.0	380	1200	1170	1100	1000	520	26.3	11.4	10	8.25
5-MSP	505501	1" FNPT	Screened		1/6	127	60	5.0	380	1200	1170	1100	1000	520	26.3	11.4	18	8.50
5-MSP	505202	1" FNPT	Screened		1/6	230	60	2.5	380	1200	1170	1100	1000	520	26.3	11.4	12	8.25

2.0

1.0

0.0

1500

30 25 20 7.0 6.0 15 4.0 3.0

FLOW - GALLONS/HOUR

FLOW - LITERS/HOUR

4000

1000

2000

500

Replacement Parts

Volute	105200
Screen	105900
Impeller	105310
Handle	105911
Adapter (GH)	599030
Seal Ring	928024

Little Giant Pump Co.