www.PumpAgents.com




Eliminator Series Sewage Ejector Pump

95 SERIES




Features


- Handles liquids and solid waste materials up to
 2 diameter.
- Cast iron pump housing with protective epoxy coating for corrosion resistance
- Oil-filled motor housing for lifetime lubrication and rapid heat dissipation
- Stainless steel fasteners
- Mechanical seals (stainless steel spring, nitrile parts, carbon and ceramic faces)
- Thermal overload protection
- Manual and Automatic models in each size.
- Automatic operation has 9 to 14 "On" level and 2 to 6 Off " level range with piggyback mechanical float switch.
- All 115 volt models are UL/CSA listed.



PumpAgents.com - Click here for Pricing/Ordering

95 SERIES SEWAGE PUMP






Specifications

MODEL NO.	ITEM NO.	LISTING	НР	VOLTS	SOLIDS SIZE (Dia. In.)	RUNNING Amps/Watts	PERFOR 5'	MANCI 10'	E (GPM 6 15'	@ HEAD) 20'	SHUTOFF (Ft.)	P.S.I.	PWR. CRD. (Ft.)	. WEIGHT (Lbs.)	DIMENSIONS (H x L x W in.)
9S-CIM 9S-CIA-RFS 9S-CIM 9S-CIA-RFS 9S-CIA-RFS*	509400 509500 509450 509520 509510	UL/CSA UL/CSA — UL/CSA UL/CSA	4/10 4/10 4/10 4/10 4/10	115 115 230 115 115	2" 2" 2" 2" 2"	13/1020 13/1020 6.5/1020 13/1020 13/1020	80 80 80 80	50 50 50 50 50	16 16 16 16	_ _ _ _	18 18 18 18 18	7.8 7.8 7.8 7.8 7.8	15 15 15* 20 15	36 36 36 37 37	11.6 x 10.3 x 6.8 11.6 x 10.3 x 6.8 11.6 x 10.3 x 6.8 11.6 x 10.3 x 6.8 11.6 x 10.3 x 6.8

^{*3&}quot; discharge RFS - Piggyback Mechanical Float Switch

* w/out plug



Construction

Cover	Nylon
Motor Housing	Epoxy Coated Cast Iron
Impeller Material	Nylon
Impeller Type	Vortex
Volute	Epoxy Coated Cast Iron
Power Cord	SJTW
Mechanical Shaft Seal	Nitrile with carbon and
	ceramic faces
Fasteners	Stainless Steel
Shaft	Steel
Bearings	Upper sintered sleeve and
	lower ball bearing

PUMP PERFORMANCE CURVE

115V 60Hz



