


Close Coupled End Suction



1. RADIAL SPLIT CASING DESIGN

Casing is close grain iron of 30,000 p.s.i. minimum tensile strength. Back pull-out design eliminates the need to disturb piping should the pump ever require service - the casing stays in the line. Centerline discharge. Stud mounted casing assures positive alignment and allows rotation of discharge to eight different positions. Openings are provided for test gauges, for venting and for draining the pump.

2. ENCLOSED BRONZE IMPELLER

Enclosed bronze impeller is of latest hydraulic design for maximum efficiency. It is balanced for vibration free operation. Precision fit to shaft and double-locked with key and cap screw.

3. REPLACEABLE CASING WEAR RING

Prevents wear on casing and is easy to replace.

4. MECHANICAL SHAFT SEAL

Mechanical Shaft Seal is self-adjusting for temperatures up to 225°F (107°C) and pressures to 150 psi (1034kpa). Has ceramic seat and carbon seal faces for long trouble-free service. Special seals are available for higher temperatures and fluids other than water. Tapped opening is provided in the seal chamber for flushing seal faces.

MAXIMUM OPERATING CONDITIONS

Maximum Pumping Temperature*	225°F (107°C)
Maximum inlet Pressure	100 PSI (690kpa)
Maximum Case Working Pressure	200 PSI (1379kpa)

* FOR STANDARD BUNA-N SEAL

MATERIALS OF CONSTRUCTION

Part	Bronze Fitted	All Bronze	All Iron
Adapter	Cast Iron	Bronze	Cast Iron
Casing	Cast Iron	Bronze	Cast Iron
Casing Wear Ring	Bronze	Bronze	Steel
Shaft	Steel	Steel	Steel
Shaft Sleeve	Bronze	Bronze	#316 Stainless
Impeller	Bronze	Bronze	Cast Iron
Shaft Seal	Carbon-Ceramic SS - Buna-N	Carbon-Ceramic SS - Buna-N	Carbon-Ceramic SS - Buna-N

5. BRONZE SHAFT SLEEVE

Gasketed and keyed hook-type sleeve protects shaft wear and corrosion in seal area.

6. MOTORS

The standard Type JM motors supplied with these pumps offer the advantages of quiet operation, controlled shaft deflection for longer mechanical seal life and bearings sized to provide good service life. All motors are **supplied by** manufacturers providing field service facilities.

7. INTERCHANGEABILITY

The complete liquid end of any size pump is interchangeable between motors on close-coupled pumps and the BURKS power frames of comparable size providing inventory flexibility, plus an option for handling emergency service.

8. FACTORY TESTED

After careful assembly and inspection, EVERY pump is factory tested and will meet Hydraulic Institute standards.

FOR TEMPERATURES TO 500°F (260°C).

All models, with the exception of the G7-2-1/2 and all G9 series pumps are available in a Jacketed Seal Cavity design for pumping hot oil, hot water and heat transfer fluids in common use in high temperature heating or cooling applications. This feature greatly extends seal life in high temperature applications. To order, add suffix "MJ" to pump catalog number for temperatures below 400°F (204°C) and add suffix "MJK" to pump catalog number for temperatures over 400°F (204°C). Example: G6-1-1/2MJ. See Section on High Temperature Pumps for more information.

SUCTION & DISCHARGE SIZES

* SERIES	SUCTION (in)	DISCHARGE (in)
G6-1-1/2	2	1-1/2
G-2 & 2F	2-1/2	2
G6-2-1/2 & 2-1/2F	3	2-1/2
G7-2 & 2F	2-1/2	2
G7A-2 & 2F	2-1/2	2
G7-2-1/2 & 2-1/2F	3	2-1/2
G9-1-1/2	2	1-1/2
G9-2 & 2F	2-1/2	2
G9-2-1/2 & 2-1/2F	3	2-1/2
G9-3F & G9A-3F	4	3
G9-4F	5	4

*F Suffix Denotes ANSI 125# Flat Face Flanges



WARNING:


CANCER AND REPRODUCTIVE HARM -
WWW.P65WARNINGS.CA.GOV

Series: G6-2F, G6-2½F, G7-2F, G7A-2F, G7-2½F

Dimensions with Flanged Casing

burks[®]
www.cranepumps.com

Close Coupled End Suction



DIMENSIONS IN INCHES																	
MODEL	MOTOR FRAME SIZE	DISC NPT (in)	SUCT NPT (in)	A	AB	B	CP	D	DD	E	F	G	H	L	O	X	Y
G6-2F	56	2	2½	5	---	8	15⅜	5⅝	4½	1⅝	---	¼	⅞	7⅞	6⅞	6	2⅞
	143JM			7	8⅝	5	15⅝	3½	4½	2¾	2	⅜	1⅝	8⅞	7⅞	6	2⅞
	145JM			7	8⅝	6	16⅝	3½	4½	2¾	2½	⅜	1⅝	8⅞	7⅞	6	2⅞
	182JM			8¾	9⅞	5¾	17⅞	4½	4½	3¾	2¼	½	1⅝	9⅞	9⅞	6	2⅞
	184JM			8¾	9⅞	6¾	18⅞	4½	4½	3¾	2¾	½	1⅝	9⅞	9⅞	6	2⅞
	213JM			10⅞	11⅞	7¼	19⅞	5¼	4½	4¼	2¾	⅝	1⅝	10¾	11	6	2⅞
	215JM			10⅞	11⅞	8¾	21⅞	5¼	4½	4¼	3½	⅝	1⅝	10¾	11	6	2⅞
G6-2½F	143JM	2½	3	7	8⅝	5	15¾	3½	5	2¾	2	⅜	1⅝	9⅞	7⅞	6½	2⅞
	145JM			7	8⅝	6	16¾	3½	5	2¾	2½	⅜	1⅝	9⅞	7⅞	6½	2⅞
	182JM			8¾	9⅞	5¾	17⅞	4½	5	3¾	2¼	½	1⅝	10⅞	9⅞	6½	2⅞
	184JM			8¾	9⅞	6¾	18⅞	4½	5	3¾	2¾	½	1⅝	10⅞	9⅞	6½	2⅞
	213JM			10⅞	11⅞	7¼	20⅞	5¼	5	4¼	2¾	⅝	1⅝	11⅞	11	6½	2⅞
	215JM			10⅞	11⅞	8¾	21½	5¼	5	4¼	3½	⅝	1⅝	11⅞	11	6½	2⅞
	254JM			12⅞	11⅞	10¼	25	6¼	5	5	4⅞	⅞	1⅝	12⅞	13⅞	6½	2⅞
G7-2F G7A-2F	143JM	2	2½	7	8⅝	5	15⅝	3½	5	2¾	2	⅜	1⅝	9⅞	7⅞	6¾	2⅞
	145JM			7	8⅝	6	16⅝	3½	5	2¾	2½	⅜	1⅝	9⅞	7⅞	6¾	2⅞
	182JM			8¾	9⅞	5¾	17⅞	4½	5	3¾	2¼	½	1⅝	9⅞	9⅞	6¾	2⅞
	184JM			8¾	9⅞	6¾	18⅞	4½	5	3¾	2¾	½	1⅝	9⅞	9⅞	6¾	2⅞
	213JM			10⅞	11⅞	7¼	19⅞	5¼	5	4¼	2¾	⅝	1⅝	11	11	6¾	2⅞
	215JM			10⅞	11⅞	8¾	21⅞	5¼	5	4¼	3½	⅝	1⅝	11	11	6¾	2⅞
	354JM			12⅞	11⅞	10¼	24⅞	6¼	5	5	4⅞	⅞	1⅝	12⅞	13⅞	6¾	2⅞
G7-2½F	256JM	2½	3	12⅞	11⅞	12¼	26¾	6¼	5	5	5	⅞	1⅝	12⅞	13⅞	6¾	2⅞
	143JM			7	8⅝	5	15¾	3½	5½	2¾	2	⅜	1⅝	9⅞	7⅞	7½	2⅞
	145JM			7	8⅝	6	16¾	3½	5½	2¾	2½	⅜	1⅝	9⅞	7⅞	7½	2⅞
	182JM			8¾	9⅞	5¾	17⅞	4½	5½	3¾	2¼	½	1⅝	10⅞	9⅞	7½	2⅞
	184JM			8¾	9⅞	6¾	18⅞	4½	5½	3¾	2¾	½	1⅝	10⅞	9⅞	7½	2⅞
	213JM			10⅞	11⅞	7¼	19⅞	5¼	5½	4¼	2¾	⅝	1⅝	11⅞	11	7½	2⅞
	215JM			10⅞	11⅞	8¾	21½	5¼	5½	4¼	3½	⅝	1⅝	11⅞	11	7½	2⅞
	254JM			12⅞	11⅞	10¼	25⅞	6¼	5½	5	4⅞	⅞	1⅝	12¾	13⅞	7½	2⅞
	256JM			12⅞	11⅞	12¼	26⅞	6¼	5½	5	5	⅞	1⅝	12¾	13⅞	7½	2⅞
	284JM			13¾	13	11½	26⅞	7	5½	5½	4¾	⅞	1⅝	12¾	14¾	7½	2⅞
	286JM			13¾	13	13	28⅞	7	5½	5½	5½	⅞	1⅝	12¾	14¾	7½	2⅞
	324JM			14½	16¼	12¼	28¾	8	5½	6¼	5¼	⅞	2⅝	13¼	17⅞	7½	2⅞
	326JM			14½	16¼	13¾	30¾	8	5½	6¼	6	⅞	2⅝	13¼	17⅞	7½	2⅞

DIMENSIONS SHOWN ABOVE ARE APPROXIMATE MAXIMUM DIMENSIONS FOR STANDARD PUMPS EQUIPPED WITH ODP MOTORS.

SECTION 2
PAGE 64
DATE 1/06



CRANE[®]

A Crane Co. Company



PUMPS & SYSTEMS

USA: (937) 778-8947 • Canada: (905) 457-6223 • International: (937) 615-3598


60 Hz Performance

Close Coupled End Suction

Close Coupled End Suction



Centrifugals - Close Coupled



1 - MOTORS				HP	FRAME SIZE
RPM & PHASE	PART NUMBER				
OPEN DRIP PROOF					
1750 RPM Single Phase (ODP)	21393	1	143JM		
	21394	1½	145JM		
	21395	2	182JM		
1750 RPM Three Phase (ODP)	21396	3	184JM		
	21419	1	143JM		
	21420	1½	145JM		
3500 RPM Single Phase (ODP)	21421	2	145JM		
	21422	3	182JM		
3500 RPM Three Phase (ODP)	09902	5	184JM		
	21850	7½	213JM		
3500 RPM Three Phase (ODP)	09906	5	182JM		
	09907	7½	184JM		
	09999	10	213JM		
3500 RPM Three Phase (ODP)	20002	15	215JM		
	21169	20	254JM		
	21170	25	256JM		
3500 RPM Three Phase (ODP)	21207	30	284JM		
TOTALLY ENCLOSED					
1750 RPM Single Phase (TEFC)	21399	1	143JM		
	21400	1½	145JM		
	21401	2	182JM		
1750 RPM Three Phase (TEFC)	21402	3	184JM		
	21403	5	213JM		
1750 RPM Three Phase (TEFC)	21426	1	143JM		
	21427	1½	145JM		
	21428	2	145JM		
3500 RPM Three Phase (TEFC)	21429	3	182JM		
	21430	5	184JM		
3500 RPM Three Phase (TEFC)	09950	5	184JM		
	09951	7½	213JM		
	20000	10	215JM		
3500 RPM Three Phase (TEFC)	20003	15	254JM		
	21195	20	256JM		
	21457	25	284JM		
3500 RPM Three Phase (TEFC)	21215	30	286JM		
EXPLOSION PROOF					
1750 RPM Three Phase (XP)	21433	1	143JM		
	21434	1½	145JM		
	21435	2	145JM		
1750 RPM Three Phase (XP)	21436	3	182JM		
	21437	5	184JM		
3500 RPM Three Phase (XP)	09954	5	184JM		
	09955	7½	213JM		
	20001	10	215JM		
3500 RPM Three Phase (XP)	20004	15	254JM		
	21196	20	256JM		
	21458	25	284JM		
3500 RPM Three Phase (XP)	21218	30	286JM		

Centrifugals - Close Coupled

SYMBOL NUMBER	PART NUMBER	QTY	DESCRIPTION
+15	09933	1	Flat Gasket +
	22083	1	O-Ring Gasket - Buna N (Std)
	22084	1	O-Ring Gasket - Viton
	22094	1	O-Ring Gasket - EPT**
	22085	1	O-Ring Gasket - Teflon
+16	21090	1	Flat Gasket +
	22140	1	O-Ring Gasket - Buna N (Std)
	22141	1	O-Ring Gasket - Viton
	22143	1	O-Ring Gasket - EPT**
	22142	1	O-Ring Gasket - Teflon
+17	09911	1	Flat Gasket +
	22083	1	O-Ring Gasket - Buna N (Std)
	22084	1	O-Ring Gasket - Viton
	22094	1	O-Ring Gasket - EPT**
	22085	1	O-Ring Gasket - Teflon
+18	21092	1	Flat Gasket +
	22089	1	O-Ring Gasket - Buna N (Std)
	22090	1	O-Ring Gasket - Viton
	22096	1	O-Ring Gasket - EPT**
	22091	1	O-Ring Gasket - Teflon
+19	20418	1	Flat Gasket +
	125857-200	1	O-Ring Gasket - Buna N (Std)
	23004	1	O-Ring Gasket - Viton
	23005	1	O-Ring Gasket - EPT**
	23006	1	O-Ring Gasket - Teflon
+20	09917	1	Mechanical Seal - Buna-N (Std)
	09926	1	Mechanical Seal - Viton
	21271	1	Mechanical Seal - EPT**
	21136	1	Mechanical Seal - Buna-N (Std)
	21189	1	Mechanical Seal - Viton
+21	21721	1	Mechanical Seal - EPT**
	21721	1	Mechanical Seal - EPT**
	21721	1	Mechanical Seal - EPT**
	21721	1	Mechanical Seal - EPT**
	21721	1	Mechanical Seal - EPT**

"CONTINUED ON NEXT PAGE"

- (*) Casing Assy. Includes Symbols 4, 9 & 14.
 (**) For hot water and Caustic service.
 (+) Series G7-2, G7A-2 & G7-2-1/2 pumps have been manufactured with either a flat or O-ring type gasket. Determine which type is required before ordering. When in doubt, order flat gasket.
 (♦) Adapter Assy. includes symbol 5.

SYMBOL NUMBER	PART NUMBER	QTY	DESCRIPTION
2	20650	1	Adapter - 143-184JM Motors
	20419	1	Adapter - 213-215JM Motors
	21086	1	Adapter Assy ♦ - 254-256 JM Motors
	21310	1	Adapter Assy ♦ - 284-286 JM Motors
3	1750 RPM		
	20420-7.00	1	Impeller - 104G7-2 & 3104G7-2
	20420-7.56	1	Impeller - 154G7-2 & 3154G7-2
	20421-6.56	1	Impeller - 104G7A-2 & 3104G7A-2
	20421-7.06	1	Impeller - 154G7A-2 & 3154G7A-2
	20421-7.63	1	Impeller - 204G7A-2 & 3204G7A-2
	21087-1-6.13	1	Impeller - 154G7-2-1/2 & 3154G7-2-1/2
	21087-1-6.50	1	Impeller - 204G7-2-1/2 & 3204G7-2-1/2
	21087-1-7.25	1	Impeller - 304G7-2-1/2 & 3304G7-2-1/2
	3450 RPM		
	20420-6.25	1	Impeller - 50G7-2 & 350G7-2
	20420-6.88	1	Impeller - 375G7-2
*4	20420-7.38	1	Impeller - 3100G7-2
	20420-7.56	1	Impeller - 3150G7-2
	20420-1	1	Impeller - 254JM Motor
	20421-5.81	1	Impeller - 50G7A-2 & 350G7A-2
	20421-6.31	1	Impeller - 375G7A-2
	20421-6.75	1	Impeller - 3100G7A-2
	20421-7.56	1	Impeller - 3150G7A-2
	20421-1-7.63	1	Impeller - 3200G7A-2
	21087-6.75	1	Impeller - 3200G7-2-1/2
	21087-7.38	1	Impeller - 3250G7-2-1/2
	21087-7.56	1	Impeller - 3300G7-2-1/2
5	22153	1	Casing Assy - G7-2 & G7A-2
	22271	1	Casing Assy - G7-2F & G7A-2F (Flanged)
	22154	1	Casing Assy - G7-2-1/2
	22272	1	Casing Assy -G7-2-1/2F (Flanged)
6	09915	1	Wear Ring - G7-2 & G7A-2
	20680	2	Wear Ring - G7-2-1/2
	04235	4	Cap Screw - Use with 20650 Adapter
	1-68-6	4	Cap Screw - Use with 20419 & 21086 Adapter
7	21289	4	Cap Screw - Use with 21310 Adapter
	20424	8	Stud
	15-6-6	8	Nut
	20059	8	Washer
8	23014	1	Key - 143-215JM Motors
	22107	1	Key - 254-286JM Motors
	01691-A	6	Pipe Plug 1/8" - Bronze
	04236	1	Pipe Plug 1/4" - Bronze
11	1-529-1	1	Cap Screw SS - 143-215JM Motors
	1-68-1	1	Cap Screw SS - 254-286JM Motors
	22105-C	1	Washer - Bronze - 143-215JM Motors
	22106	1	Washer - Bronze - 254-286JM Motors

WARNING:

CANCER AND REPRODUCTIVE HARM -
 WWW.P65WARNINGS.CA.GOV



Centrifugals - Close Coupled

SYMBOL NUMBER	PART NUMBER	QTY	DESCRIPTION
DIFFERING PARTS FOR ALL IRON CONSTRUCTION			
2	21086-B	1	Adapter Assy ♦ - 254-256 JM Motors
	21310-B	1	Adapter Assy ♦ - 284-286 JM Motors
3	20420-A	1	Impeller - Iron
	20421-A	1	Impeller - Iron
	20421-A-1	1	Impeller - Iron
	21087-A	1	Impeller - Iron
Size suffixes same as standard bronze impellers			
6	03288	4	Cap Screw - for 20650-A Adapter
8	01638-B	4	Cap Screw - for 20419-B & 21086-A Adapter
	03160-A	8	Nut
*4	22153-B	1	Casing Assy - G7-2 & G7A-2
	22271-B	1	Casing Assy - G7-2F & G7A-2F (Flanged)
	22154-B	1	Casing Assy - G7-2-1/2
	22272-B	1	Casing Assy -G7-2-1/2F (Flanged)
5	09915-A	1	Wear Ring - G7-2 & G7A-2
	20680-A	2	Wear Ring - G7-2-1/2
11	00158	6	Pipe Plug 1/8" - Steel
12	04236-A	1	Pipe Plug 1/4" - SS
14	22105-A	1	Washer - Steel - 143-215JM Motors
	22106-A	1	Washer - Steel - 254-286JM Motors
20	22063-A	1	Shaft Sleeve - Bronze - 143-215JM Motors
	22066-A	1	Shaft Sleeve - Bronze - 254-286JM Motors

(*) Casing Assy. Includes Symbols 4, 9 & 14.

(**) For hot water or Caustic service.

(+) Series G7-2, G7A-2 & G7-2-1/2 pumps have been manufactured with either a flat or O-ring type gasket. Determine which type is required before ordering. When in doubt, order flat gasket.

(♦) Adapter Assy. includes symbol 5.

SYMBOL NUMBER	PART NUMBER	QTY	DESCRIPTION
PUMPS with 143-215JM Motors			
19	22080	1	O-Ring Gasket - Buna N (Std)
	2-31005-012	1	O-Ring Gasket - Viton
	22093	1	O-Ring Gasket - EPT**
	22082	1	O-Ring Gasket - Teflon
PUMPS with 254-286JM Motors			
20	22086	1	O-Ring Gasket - Buna N (Std)
	22087	1	O-Ring Gasket - Viton
	22095	1	O-Ring Gasket - EPT**
	22088	1	O-Ring Gasket - Teflon
21	22063-C	1	Shaft Sleeve - Bronze - 143-215JM Motors
	22066	1	Shaft Sleeve - Bronze - 254-286JM Motors
21	09918	1	Slinger Washer - 143-215JM Motors
	21093	1	Slinger Washer - 254-286JM Motors
DIFFERING PARTS FOR ALL BRONZE CONSTRUCTION			
2	20650-A	1	Adapter - 143-184JM Motors
	20419-B	1	Adapter - 213-215JM Motors
	21086-A	1	Adapter Assy ♦ - 254-256JM Motors
	21310-A	1	Adapter Assy ♦ - 284-286JM Motors
*4	22153-A	1	Casing Assy - G7-2 & G7A-2
	22271-A	1	Casing Assy - G7-2F & G7A-2F (Flanged)
	22154-A	1	Casing Assy - G7-2-1/2
	22272-A	1	Casing Assy -G7-2-1/2F (Flanged)
13	03289	1	Cap Screw, Bronze - 143-215JM Motors
	01638-B	1	Cap Screw, Bronze - 254-286JM Motors

WARNING:

CANCER AND REPRODUCTIVE HARM -
WWW.P65WARNINGS.CA.GOV

