
Burks Pumps 37GA4-1-1/4
www.PumpAgents.com - Click here for Pricing/Ordering for Pumps and Parts

Series: GA4-¾, GA4-1, GA4-1¼, GA4-1½


Close Coupled End Suction



3500 RPM - 60Hz.

CAPACITIES TO 130 GPM (8.2 LPS)
HEADS TO 75 FEET (23 M)


(*) FOR CAPACITIES ABOVE 100 GPM SEE GA4-1½ CURVE.



2900 RPM - 50Hz.

CAPACITIES TO 108 GPM (6.8 LPS)
HEADS TO 50 FEET (15 M)

Individual performance curve should be checked for final selection.



Burks Pumps 37GA4-1-1/4
www.PumpAgents.com - Click here for Pricing/Ordering for Pumps and Parts

Series: GA4-¾, GA4-1, GA4-1¼, GA4-1½

Features

www.cranepumps.com

Close Coupled End Suction

FOUR POSITION CASING
Discharge can be located in any of four positions. Casing is close grain iron of 30,000 psi minimum tensile strength. Back pull-out design eliminates the need to disturb piping should the pump ever require service - the casing stays in the line.

ENCLOSED CAST IRON IMPELLER
Of the latest hydraulic design for maximum efficiency, impeller is balanced for vibration-free operation and threaded onto stainless steel motor shaft.Impeller is available in bronze.

MECHANICAL SHAFT SEAL
Standard self-adjusting shaft seal for temperatures to 225°F (107°C) and pressures to 150 psi (1034 kpa). Ceramic seat and carbon seal face for long trouble-free service. Special seals are available for higher temperatures and fluids other than water.

MOTORS
Standard pump motors are of open drip proof (ODP) construction and are rated with jet pump service factors for continuous duty operation. Motors are 56 frame size with NEMA standard mounting flange, one piece threaded stainless steel shaft and ball/ball bearing construction.

FACTORY TESTED
After careful assembly and inspection, EVERY pump is factory tested and meets Hydraulic Institute standards.

MAXIMUM OPERATING CONDITIONS	
TEMPERATURE (For Standard Buna-N Seal)	225ºF (107ºC)
INLET PRESSURE	70 PSI (433kPa)
CASING WORKING PRESSURE	100 PSI (690kPa)

MOTOR INFORMATION
60 Hz - 3500 RPM - ODP
Single Phase: 1/3 thru 2 Hp. - 115/230 Volt
3 Hp. - 230 Volt only
Three Phase: 1/3 thru 3 Hp. - 208-230/460 Volt

50 Hz - 2900 RPM - ODP
Single Phase: 110/220 Volt
Three Phase: 380 Volt

Voltages may differ from some suppliers. Consult factory.
Overload Protection: All single phase ODP and Totally Enclosed motors have built-in overload protection. All three phase motors and all explosion proof motors must be installed with a magnetic starter which provides full 3-leg protection. Failure to use correct starter and overloads will void motor warranty.

MATERIALS OF CONSTRUCTION			
PART	**ALL IRON**	**BRONZE FITTED**	**ALL BRONZE**
Adapter	Cast Iron	Cast Iron	Bronze
Casing	Cast Iron	Cast Iron	Bronze
Impeller	Cast Iron	Bronze	Bronze
Shaft	#303 Stainless	#303 Stainless	#303 Stainless
Shaft Seal	Carbon-Ceramic SS - Buna-N	Carbon-Ceramic SS - Buna-N	Carbon-Ceramic SS - Buna-N

WARNING:
CANCER AND REPRODUCTIVE HARM -
WWW.P65WARNINGS.CA.GOV


CRANE
A Crane Co. Company
PUMPS & SYSTEMS
USA: (937) 778-8947 • Canada: (905) 457-6223 • International: (937) 615-3598

Burks Pumps 37GA4-1-1/4
www.PumpAgents.com - Click Here for Pricing, Ordering for Pumps and Parts

Series: GA4-¾, GA4-1, GA4-1¼, GA4-1½

Dimensions

Close Coupled End Suction



DIMENSIONS IN INCHES																		
MODEL	MOTOR FRAME SIZE	DISC NPT (in)	SUCT. NPT (in)	A	B	CP	D	DD	E	F	G	L	O	OP	P	X	Y	Z
GA4-¾	56	¾	1	6	5	15½	3½	3 5/16	2½	3	3/16	5½	6¾	7	1⅛	3½	2 1/16	2⅝
GA4-1	56	1	1¼	6	5	15 9/16	3½	3 5/16	2½	3	3/16	5 9/16	6¾	7	1⅛	3½	1 15/16	2 11/16
GA4-1¼	56	1¼	1½	6	5	15 13/16	3½	3 5/16	2½	3	3/16	5 15/16	6¾	7½	1⅛	4	2 3/16	3
GA4-1½	56	1½	2	6	5	16 1/16	3½	3 7/16	2½	3	3/16	6 1/16	6¾	8	1⅛	4½	2 5/16	3⅛

DIMENSIONS IN MILLIMETERS																		
MODEL	MOTOR FRAME SIZE	DISC NPT (in)	SUCT. NPT (in)	A	B	CP	D	DD	E	F	G	L	O	OP	P	X	Y	Z
GA4-¾	56	¾	1	152	127	394	89	84	64	76	4.8	140	172	178	29	89	52	67
GA4-1	56	1	1¼	152	127	395	89	84	64	76	4.8	141	172	178	29	89	49	68
GA4-1¼	56	1¼	1½	152	127	402	89	84	64	76	4.8	151	172	191	29	102	55	76
GA4-1½	56	1½	2	152	127	408	89	87	64	76	4.8	154	172	203	29	114	59	79

DIMENSIONS SHOWN ABOVE ARE APPROXIMATE MAXIMUM DIMENSIONS FOR STANDARD PUMPS EQUIPPED WITH ODP MOTORS.


Burks Pumps 37GA4-1-1/4
www.PumpAgents.com - Click here for Pricing/Ordering for Pumps and Parts


Series: GA4-1¼

60 Hz Performance

burks®
www.cranepumps.com

Close Coupled End Suction





CRANE®
A Crane Co. Company

PUMPS & SYSTEMS

USA: (937) 778-8947 • Canada: (905) 457-6223 • International: (937) 615-3598


Series: GA4-1¼

50 Hz Performance


burks®
www.cranepumps.com

Close Coupled End Suction

2900 RPM




2900 RPM



Series: GA4

burks®
www.cranepumps.com

Centrifugals - Close Coupled



1 - MOTORS (All 56J Frame)			
	RPM & PHASE	PART NUMBER	HP
OPEN DRIP PROOF	3500 RPM Single Phase (ODP)	003-211-371-02	1/3
		005-211-371-02	1/2
		007-211-371-02	3/4
		010-211-371-02	1
		015-211-371-02	1½
		020-211-371-02	2
	3500 RPM Three Phase (ODP)	003-230-361-02	1/3
		005-230-361-02	1/2
		007-230-361-02	3/4
		010-230-361-02	1
		015-230-361-02	1½
		020-230-361-02	2
TOTALLY ENCLOSED	3500 RPM Single Phase (TENV / TEFC)	005-211-372-02	1/2
		007-211-372-02	3/4
		010-211-372-02	1
		015-211-372-02	1½
		020-211-372-02	2
	3500 RPM Three Phase (TENV / TEFC)	005-230-362-02	1/2
		007-230-362-02	3/4
		010-230-362D02	1
		015-230-362D02	1½
		020-230-362D02	2
EXPLOSION PROOF	3500 RPM Single Phase (XP)	005-211-374-02	1/2
		007-211-374-02	3/4
		010-211-374-02	1
		015-211-374-02	1½
		020-211-374-02	2
	3500 RPM Three Phase (XP)	005-230-364-02	1/2
		007-230-364-02	3/4
		010-230-364-02	1
		015-230-364-02	1½
		020-230-364-02	2

SYMBOL NUMBER	PART NUMBER	QTY	DESCRIPTION
2	08105	1	Slinger Washer
3	0115478	1	Adapter
4	03122	4	Cap Screw, 3/8-16 x 3/4" Lg
5	Q15-5-E26	4	Cap Screw, 3/8-16 x 7/8" Lg
6	00158	4	Pipe Plug 1/8"
7	0115488	1	Casing, GA4-3/4
	0115490	1	Casing, GA4-1
	0115492	1	Casing, GA4-1-1/4
	0115494	1	Casing, GA4-1-1/2
8	0115432-3.75	1	Impeller, Brass, 3GA4 & 33GA4-3/4
	0115432-4.00	1	Impeller, Brass, 5GA4 & 35GA4-3/4
	0115432-4.25	1	Impeller, Brass, 7GA4 & 37GA4-3/4
	0115436-3.25	1	Impeller, Brass, 3GA4 & 33GA4-1
	0115436-3.75	1	Impeller, Brass, 5GA4 & 35GA4-1
	0115436-4.00	1	Impeller, Brass, 7GA4 & 37GA4-1
	0115436-4.25	1	Impeller, Brass, 10GA4 & 310GA4-1
	0115440-3.25	1	Impeller, Brass, 3GA4 & 33GA4-1-1/4
	0115440-3.50	1	Impeller, Brass, 5GA4 & 35GA4-1-1/4
	0115440-3.75	1	Impeller, Brass, 7GA4 & 37GA4-1-1/4
	0115440-4.00	1	Impeller, Brass, 10GA4 & 310GA4-1-1/4
	0115440-4.25	1	Impeller, Brass, 15GA4 & 315GA4-1-1/4
	0115444-3.25	1	Impeller, Brass, 5GA4 & 35GA4-1-1/2
	0115444-3.50	1	Impeller, Brass, 7GA4 & 37GA4-1-1/2
	0115444-3.75	1	Impeller, Brass, 10GA4 & 310GA4-1-1/2
	0115444-4.25	1	Impeller, Brass, 15GA4 & 315GA4-1-1/2

SYMBOL NUMBER	PART NUMBER	QTY	DESCRIPTION
9	08514	1	Mechanical Seal
10	00158	1	Pipe Plug 1/8"
11	0115519	1	Base
12	20459	1	Nut
13	0115516	1	Case Gasket

WARNING:
CANCER AND REPRODUCTIVE HARM -
WWW.P65WARNINGS.CA.GOV

CRANE
A Crane Co. Company
PUMPS & SYSTEMS
USA: (937) 778-8947 • Canada: (905) 457-6223 • International: (937) 615-3598
www.cranepumps.com