
Model: 17200-0001

obsolety- use Sherward 6-50



MODEL 17200-0001

SELF-PRIMING PUMPS FEATURES

Body:

Bronze

Impeller:

Jabsco Neoprene Compound

Shaft:

Stainless Steel

Shaft Seal:

Carbon-ceramic Face-type

Ports:

114" hose connection

Pulley:

71/2" OD, for "A" size belt

APPLICATION

Marine Engine Cooling for Chrysler Engines

LM 318 (225) after serial number 117181


LM 340 (250) after serial number 117181

LM 383 (260) after serial number 117181

M 400 (280) after serial number 117181

M 440 (300, 330, 335 and 375) after serial number

Replaces Chrysler pump numbers 3527374 and 3675763



INSTALLATION INSTRUCTIONS

Mount pump on engine bracket. Make sure pump pulley is aligned with drive pulley. Tighten belt by moving bracket. Allow about 1/2" movement in belt when tightened. Slip inlet and outlet hoses over ports and clamp securely.

WARNING: EXPOSED PULLEYS AND BELTS CAN CAUSE INJURY, INSTALL SHIELD AROUND PULLEYS AND BELTS.

OPERATING INSTRUCTIONS

Pump will self-prime at low or high speeds. Make sure scoop and inlet line are clear and all connections airtight. Do not run pump dry for more than 30 seconds. Lack of water flow may damage impeller. To drain pump, loosen end cover screws.

SH Gr-50+Gr Jone except pully hameter

PumpAgents.com - buy pumps and parts online

Model: 17200-000