3-MD



Features

- Thermally Protected, Open, Fan-Cooled Motor
- Ball Bearings
- 6' Power Cord with 3-Prong Plug (No plug on 230V)
- Specific Gravity to 1.1
- Fluid Temperature to 150 Degrees F.
- Ambient Air Temperature to 77 Degrees F.
- NOTE: Consult your local distributor or the factory for applications with higher ambient temperatures, specific gravities and viscosities.

Construction


- Volute Glass-filled Polypropylene
- Housing Glass-filled Polypropylene
- Impeller Glass-filled Polypropylene
- Shaft Titanium
- Thrust Washers Titanium
- O-Ring Nitrile

The Little Giant MD series features leakproof, seal-less magnetic drives and are designed for in-line, non submersible use. Volute and magnet housing are glass-filled polypropylene for excellent chemical resistance. Impeller is glass-filled polypropylene and Ceramagnet "A" (Barium Ferrite). Shaft and thrust washers are

www.PumpAgents.com

PumpAgents.com - Click here for Pricing/Ordering


3-MD




NOTE: Designs and dimensions may vary for various reasons (i.e. type of motor). This information should be used as general guide rather than an unqualified guarantee. Specifications are subject to change without prior notice.

Specifications

Model	Item									Perf	orman	ce (GP	H @ H	ead)	Shut	t Off	Pwr. Cord	Weight
No.	No.	Intake	Discharge	Listing(s)	HP	Volts	Hertz	Amps	Watts	1'	3'	6'	9'	15"	Feet	PSI	(ft)	(Lbs.)
3-MD	581002	1/2" FNPT	1/2" MNPT	UR/C-CSA	1/20	115	60	1.4	105	590	545	490	390	150	16.3	7.1	6	7.50
3-MD	581098	1/2" FNPT	1/2" MNPT	PL	PUMP HEAD LESS MOTOR												1.67	



FLOW - LITERS/HOUR



Replacement Parts

ITEM	PART NO.	DESCRIPTION					
A	180079	Volute					
В	924007	O-Ring					
С	921067	Thrust Washer					
D	181165	Impeller					
Е	180058	Shaft					
F	180004	Housing					
1	920003	Wing Nut					
2	911403	Stud, Collared					
3	180602	Drive Magnet					
4	180031	Mtg. Bracket					

Note: Parts A-F Contact Fluid.

Little Giant Pump Co.