

SPECIFICATIONS:

MODEL NUMBER: 8000-643-236

PUMP DESIGN: Positive Displacement 3 Chamber Diaphragm Pump

CAM: 3.0 Degree

MOTOR: Permanent Magnet, P/N 11-111-00

VOLTAGE: 12 VDC Nominal

PRESSURE SWITCH: Adjustable Shut-Off (Range 40-60 PSI)

Factory Set @ 60 PSI, Turn On 45 PSI ± 5 PSI

LIQUID TEMPERATURE: 180 Degrees Fahrenheit (82 Degrees Centigrade) Max.

PRIME: Self-Priming Up To 11 Ft. Vertical,

PORTS: 3/8"-18 NPT Female

MATERIAL OF CONSTRUCTION:

PLASTICS- Nylon

VALVES- Buna-n

DIAPHRAGM- Geolast (Main), Buna-n (Switch)


FASTENERS- Zinc Plated Steel



NET WEIGHT: 4.1 Lbs (1.9 Kg)

DUTY CYCLE: Continuous (See Temperature Rise Chart)

TYPICAL APPLICATIONS: Agricultural Spraying

DIMENSIONS:



TEMPERATURE RISE**TYPICAL PERFORMANCE**

PRESSURE (PSI)	FLOW (GPM/LIT)	RPM MIN/MAX	CURRENT (AMPS)	VOLTAGE (VOLTS)
OPEN	1.8/6.8	2350/2420	2.7	12VDC
10	1.49/5.6	2280/2370	3.3	"
20	1.44/5.4	2235/2310	4.1	"
30	1.39/5.2	2175/2240	4.8	"
40	1.33/5.0	2120/2190	5.4	"
50	1.27/4.8	2075/2140	6.1	"
60	1.22/4.6	2035/2095	6.8	"

-SPECIFICATIONS SUBJECT TO CHANGE WITHOUT NOTICE.

-ALL DATA BASED ON TESTING WITH WATER AT AMBIENT TEMPERATURE.